

# USAC .25 MIDGET BULLETIN 2/25/14

## APPENDIX I

*F. The front tire diameter must be no more than 11" diameter. The rear tire diameter must be no more than 12.5" diameter.*

## WORLD FORMULA TECH MANUAL

### **ROCKER ARMS, ROCKER BALL, AND ROCKER ARM STUDS**

*6. Rocker arm length ~~2.865~~ 2.850 inches minimum.*

## ANIMAL TECH MANUAL

### **ROCKER ARMS, ROCKER BALL, AND ROCKER ARM STUDS**

*5. Rocker arm - overall length ~~2.865~~ 2.850 inches minimum.*

*10. Rocker arm ~~overall length 2.865 inches min.~~*

## SHOCK AND SPRING BULLETIN CLARIFICATION

We have received many calls in regards to the new quarter midget springs rule. There are many racers that have older springs that are not marked with either a manufacture or a part number. Many if not all of these springs are ALLOWED as they are "linear wound design springs" per Rule 711 Steering and Suspension - Sec. H - #2. The linear wound spring is the typical spring that has been used for years in quarter midget racing. If the spring you are using is not listed in the approved spring list this doesn't mean it is illegal as long as it is a standard linear wound spring.

The approved list includes the spring manufactures that sent us a description of their springs along with part numbers for each spring. If we didn't get a part number for the spring we didn't list them but doesn't mean they are illegal.